

Fina Circle 200 15-840-1420LM



Technical Details:

Luminous Flux:	1400 lm
LED Output:	13.5 W
Light Yield:	93 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
Ignition Time:	<0,5 s
Input Current:	AC 100-240V, 230mA, 50/60Hz
Power Consumption:	15 W
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 40-63V, 280mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	200x22 mm
Installation Depth:	22 mm
Cut-Out Dimensions:	184 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	394 g
Type of Packaging:	box
Weight incl. Packaging:	0.37 kg
Content Master Package:	30
Dimensions of Master Package:	560 x210 x 410 mm
Weight Master Package:	12 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	35.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557810744

Information and Downloads:

