

# Newtura Round 500 40-830/840-4200LM CCT-/Power Select



## Product information "Newtura Round 500 40-830/840-4200LM CCT-/Power Select"

### Ceiling light

Newtura is a round surface-mounted luminaire with an integrated LED driver. Optionally also available as a dimmable version (Dali or 0-10V). The integrated Driver has a power select switch to adjust the output level: 32W, 36,5W, 38W and 40W. The light color can be selected as well: 3000K, 3500K, 4000K. Easy assembly thanks to separate mounting plate and twist lock with additional fall protection using a safety rope. Integrated electrical terminal block for power loop. Can also be suspended using a rope set. On request, the lamp can also be equipped with an internal microwave sensor or battery emergency light pack. As a dimmable variant with Meanwell® LC-45 driver, it is also suitable for operation on emergency power central battery systems in accordance with EN 60598-2-22. Due to the large internal space, emergency switch relays can also be integrated. High quality Samsung LED chips for long life and high luminous flux maintenance. Elegant and high-quality die-cast aluminum housing. Universal mounting options.



### Technical Details:

Luminous Flux	4200 lm
Light Yield:	105 lm/W
Light Temperature:	3000,3500,4000 K
Color Rendering Index (CRI)	≥85 Ra
Color Consistency (SDCM):	4
Power Consumption:	34,36,38,40 W
Power Factor (PF):	0.96
Operating Hours:	>50.000 h L80/B20
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 40°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Dimensions	500x50 mm
Net Weight:	5250 g
Warranty	5 years

### Information and Downloads:

