Product Information

**Order number: LG30456**

# Alvera Line MKII 1200 40-CCT Select-5600LM IFS

## Product information "Alvera Line MKII 1200 40-CCT Select-5600LM IFS"

LED Tri-proof light
The Litegear® Alvera is a stylish, waterproof LED fixture with IP65 standard and high mechanical protection. Alvera Line LED is equipped with LED boards with very high system efficency up to 130 Lumen/Watt and available in different lengths and in different power classes.
Based on a strong aluminum profile with excellent heat dissipation for long lifespan of up to 50.000 hours and a opal PC diffuser Litegear® created a unique LED weatherproof luminaire with easy and fast installation and daisy chain function trough easy access endcaps and junction terminal. The Select Version has additional CCT Select function: 4000, 5000 or 6000 Kelvin. Alvera has a fast cash back due to its excellent performance and high efficency up to 7500 Lumen. Alvera is the perfect luminaire for industrial applications in factories, warehouse, coolhouse storage, parking lots, sellers or just outside. Up to 5 years full warranty (or max. 25000 hours of use)!
Alvera comes with a high quality LED driver!
Suitable for use in HACCP, IFS, and/or BRC lobal Standard Food certified companies.

## Technical Details:

| | |
|---|---|
| **Luminous Flux** | 5600 lm |
| **Light Yield:** | 144 lm/W |
| **Light Temperature:** | 4000,4500,5500 K |
| **Color Rendering Index (CRI)** | ≥83 Ra |
| **Color Consistency (SDCM):** | 5 |
| **Power Consumption:** | 39 W |
| **Power Factor (PF):** | 0.96 |
| **Operating Hours:** | >50.000 h L80/B10 |
| **Switching Cycles:** | >50.000 |
| **Ignition Time:** | <0,5 s |
| **Ambient Temperature (TA):** | -15°C - 50°C |
| **Housing Material:** | aluminum |
| **Housing Color** | white Alu |
| **Dimensions** | 1225x85x78 mm |
| **Net Weight:** | 2900 g |
| **Warranty** | 5 years |

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de