


Alvera Line MKII 1200 40-CCT Select-5600LM IFS



Technical Details:

Luminous Flux:	5600 lm
LED Output:	37 W
Light Yield:	144 lm/W
Light Temperature:	4000,4500,5500 K
Light Color:	CCT Select
Color Rendering Index:	≥83 Ra
Color Consistency (SDCM):	<5
Beam Angle:	120 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 2835
Number of LED:	468
Ignition Time:	<0,5 s
Input Current:	AC 180-264maxV, 171mA, 50Hz
Power Consumption:	39 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.96
Input Driver:	terminal
Output of Driver:	DC 27-40V, 950mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-15°C - 50°C
Storage Temperature:	-25°C - 55°C

Dimensions:	1225x85x78 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	white Alu
Housing Material:	aluminum
Special Feature of Housing:	opt. Polycarbonat Cover
Cover:	opal
Net Weight:	2900 g
Type of Packaging:	box
Dimensions of Packaging:	1295x92x82
Weight incl. Packaging:	3.125 kg
Content Master Package:	4
Dimensions of Master Package:	1320x190x220 mm
Weight Master Package:	11 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557820958
Einfache, und schnelle Montage In/out	
Schnellverschluß Endkappen	
Lichtfarebe wählbar: 4000, 4500, 5500K	
optional auch als dimmbare Version Dali, 1-10V	
optional auch mit Bewegungsmelder lieferbar	

Information and Downloads:

