


Alvera Line MKII 1500 60-CCT Select-8400LM IFS



Technical Details:

Luminous Flux:	8400 lm
LED Output:	56 W
Light Yield:	140 lm/W
Light Temperature:	4000, 5000, 6000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	120 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	650
Ignition Time:	<0,5 s
Input Current:	AC 180-264V, 235mA, 50/60Hz, DC 200-264V
Power Consumption:	60 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 27-40V, 1450mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-15°C - 50°C
Storage Temperature:	-25°C - 55°C

Dimensions:	1525x85x78 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	white
Housing Material:	aluminum
Coating:	anodised
Special Feature of Housing:	Alu + Polycarbonat
Cover:	opal
Net Weight:	3500 g
Type of Packaging:	box
Dimensions of Packaging:	1600x92x82
Weight incl. Packaging:	3.875 kg
Content Master Package:	4
Dimensions of Master Package:	1620x190x220 mm
Weight Master Package:	15,5 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557820941
Einfache, und schnelle Montage, In/Out	
Schnellverschluss Endkappen	
Farbwahl: 4000, 4500, 5500K	
optional auch als dimmbare Version Dali, 1-10V	
optional auch mit Bewegungsmelder lieferbar	

Information and Downloads:

