
Product Information


Order number: LG14380W

DURATA LINE 20-830-2000LM FL









Technical Details:

Luminous Flux	2000 lm
Light Yield:	100 lm/W
Light Temperature:	3000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	20 W
Power Factor (PF):	0.95
Operating Hours:	>50.000 h L80/B10
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Dimensions	990x50x95 mm
Net Weight:	1935 g
Warranty	5 years

Product information "DURATA LINE 20-830-2000LM FL"

Linear Office LED light line system

Durata Line is a modular LED light line system for offices, schools and retail spaces. Several modules can be connected electrically and mechanically. The lights can be fastened directly to the ceiling with clips or suspended using steel cable sets. Durata Line is available in different versions such as different beam angles, light colors and optimized glare control, for example for computer workstations. Available housing colors: black or white

Technical specifications:

- modular light line system for Office, shop or schools
- High energy savings through high system efficiency of up to 105 lumens / watt
- optionally also available with dimmable drivers
- eye-friendly optics with optimized glare control UGR < 19 and flicker-free light

selectable beam angle:
100 ° UGR: 22, 70 ° UGR < 19 ;, 66 ° UGR < 13, 43 ° UGR < 6, asymmetric 60 °

Information and Downloads: