Technical Data Sheet

Order number: LG60010


LITEGEAR
LED Lighting Solutions

Emergy Brick 3-858-150lm WH









Technical Details:

Luminous Flux:	150 lm
LED Output:	3 W
Light Yield:	50 lm/W
Light Temperature:	5800 K
Light Color:	cold white
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	16
Ignition Time:	<1 s
Input Current:	AC 220-240VV, 50Hz
Power Consumption:	3 W
Contains Driver:	✓
Power Factor (PF):	>0.5
Input Driver:	terminal
Input Lamp:	terminal
Switching Cycles:	>20.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C

Dimensions:	345x110x60 mm
Installation Depth:	30 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
Housing Color	white
Housing Material:	Polycarbonat
Cover:	clear
Net Weight:	600 g
Type of Packaging:	box
Weight incl. Packaging:	0.72 kg
Content Master Package:	12
Dimensions of Master Package:	410x375x255 mm
Weight Master Package:	9 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	40.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
inkl. Batterie Accupack 3h Notlicht 3,6V 1500mA	
Ni-Cd Batterie	
optional ist ein Deckeneinbaurahmen erhältlich	
Batteriebetrieb: 135lm	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de