Technical Data Sheet

Order number: LG10950A

Luna Plane IP66 Floodlight 12-830-1290LM







Technical Details:

Luminous Flux:	1290 lm
LED Output:	11 W
Light Yield:	108 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
LED-Chip Manufacturer:	Seoul Semiconductor
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 85 - 265V, 50/60Hz
Power Consumption:	12 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with plug
Output of Driver:	DC 36 - 42V, 300mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	205x150x42 mm
Mounting:	ceiling,wall,ground
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Net Weight:	1121 g
Type of Packaging:	box
Dimensions of Packaging:	193x78x240
Weight incl. Packaging:	1.226 kg
Content Master Package:	12
Dimensions of Master Package:	500x390x260 mm
Weight Master Package:	15,47 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,GS
Barcode:	4250557812281

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de