


Alwetra 1500 48-75W-840-9750LM Narrow Beam



Technical Details:

Luminous Flux:	9750 lm
LED Output:	72 W
Light Yield:	130 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	60 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	1-10V
LED-Chip:	SMD
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	75 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	terminal
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	1502x52x72 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	white
Housing Material:	aluminum
Special Feature of Housing:	polycarbonate
Cover:	klar mit Linsen
Net Weight:	2420 g
Weight incl. Packaging:	2.42 kg
Content Master Package:	6
Dimensions of Master Package:	1620x250x300 mm
Weight Master Package:	14,8 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557820491
Einfache, und schnelle Montage, In/Out	
optionale Batterienotlichtmodule lieferbar	
wählbare Ausgangsleistung: 48, 61, 72, 75W	
dimmbare Version: 1-10V, Phasenwahl L1-L3	
optional auch mediums Bewegungsmelder steuerbar	

Information and Downloads:

