


Cappila XTreme 1500 45-840-6500lm



Technical Details:

Luminous Flux:	6500 lm
LED Output:	45 W
Light Yield:	144 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
LED-Chip:	SMD 2835
Number of LED:	416
Ignition Time:	<0,5 s
Input Current:	AC 200 - 240V, 50/60Hz
Power Consumption:	45 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 30-42V, 1050mA
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	75x1500 mm
Length of Tube:	1500 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	69
IK Code:	10
Housing Color	white
Housing Material:	Polycarbonat
Special Feature of Housing:	Tube
Cover:	opal
Net Weight:	2488 g
Type of Packaging:	box
Dimensions of Packaging:	1640x80x80
Weight incl. Packaging:	2.751 kg
Content Master Package:	6
Dimensions of Master Package:	1650x175x250 mm
Weight Master Package:	17,4 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	70.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557812069

Information and Downloads:



