

Osira HighBay MKII 100-857-14000LM DIM



Technical Details:

Luminous Flux:	14000 lm
LED Output:	97 W
Light Yield:	140 lm/W
Light Temperature:	5700 K
Light Color:	daylight
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	1-10V,PWM
LED-Chip Manufacturer:	Cree
LED-Chip:	SMD 2835
Number of LED:	168
Ignition Time:	<0,5 s
Input Current:	AC 100-305V, 430mA, 50/60Hz
Power Consumption:	100 W
Contains Driver:	✓
Driver Manufacturer:	Sosen
Power Factor (PF):	>0.97
Input Driver:	cable with flying leads
Output of Driver:	DC 90-130V, 700-1000mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-40°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	245x184 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	65
IK Code:	08
Housing Color	black
Housing Material:	aluminum
Coating:	lacquered
Cover:	clear
Net Weight:	2255 g
Type of Packaging:	box
Dimensions of Packaging:	295x295x265
Weight incl. Packaging:	3.174 kg
Content Master Package:	1
Dimensions of Master Package:	295x295x295 mm
Weight Master Package:	3,175 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557821412
Magnesium Alloy Gehäuse/housing	
TGIC Beschichtung/Coating	
UGR <25 mit 60° Reflektor	
optional auch mit whiteem Gehäuse lieferbar	
optional in white housing available	

Information and Downloads:

