


Cappila XTreme MKIII 1500 60-840-8700lm



Technical Details:

Luminous Flux:	8700 lm
Light Yield:	145 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	240 °
Unified Glare Rating (UGR):	<25
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	60 W
Contains Driver:	✓
Driver Manufacturer:	Tridonic
Power Factor (PF):	>0.92
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 60°C

Dimensions:	70x1490 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	69
IK Code:	10
Housing Color	white/Chrom
Housing Material:	Polycarbonat
Special Feature of Housing:	Tube
Cover:	opal
Net Weight:	1807 g
Type of Packaging:	box
Dimensions of Packaging:	1580x90x90
Weight incl. Packaging:	2.025 kg
Content Master Package:	10
Dimensions of Master Package:	1615x435x200 mm
Weight Master Package:	21,85 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405494000
Certifications	CE,LM80
Barcode:	4250557821207

Information and Downloads:

