

# Xona Maxima Basic Unit 150FL 55/70-840-11200LM Power Select



## Technical Details:

|                                    |                                               |
|------------------------------------|-----------------------------------------------|
| Luminous Flux:                     | 11200 lm                                      |
| LED Output:                        | 67 W                                          |
| Light Yield:                       | 160 lm/W                                      |
| Light Temperature:                 | 4000 K                                        |
| Light Color:                       | neutralwhite                                  |
| Color Rendering Index:             | ≥80 Ra                                        |
| Color Consistency (SDCM):          | <4                                            |
| Beam Angle:                        | 90 °                                          |
| Unified Glare Rating (UGR):        | <25                                           |
| Light Emission:                    | downward                                      |
| LED-Chip Manufacturer:             | Epistar                                       |
| LED-Chip:                          | SMD 2835                                      |
| Ignition Time:                     | <0,5 s                                        |
| Input Current:                     | AC 180 - 264V, 470mA,<br>50/60Hz, DC 170-230V |
| Power Consumption:                 | Power Select (55, 60, 65, 70 W)               |
| Contains Driver:                   | ✓                                             |
| Driver Manufacturer:               | Litegear                                      |
| Power Factor (PF):                 | >0.95                                         |
| Input Driver:                      | terminal                                      |
| Output of Driver:                  | DC 55-70V, 780-1000mA                         |
| CC/CV:                             | CC                                            |
| Input Lamp:                        | plug connector                                |
| Switching Cycles:                  | >100.000                                      |
| Electrical Protection Class:       | I                                             |
| Compatible with Emergency Current: | ✓                                             |
| Ambient Temperature (TA):          | -20°C - 50°C                                  |
| Storage Temperature:               | -40°C - 60°C                                  |

|                                                    |                   |
|----------------------------------------------------|-------------------|
| Dimensions:                                        | 1498,5x70x39,4 mm |
| Mounting:                                          | Decke             |
| Montageart:                                        | surface mounted   |
| IP Class:                                          | 30                |
| IK Code:                                           | 02                |
| Housing Color                                      | white             |
| Housing Material:                                  | steel             |
| Coating:                                           | coated            |
| Cover:                                             | clear             |
| Net Weight:                                        | 1780 g            |
| Type of Packaging:                                 | box               |
| Weight incl. Packaging:                            | 1.85 kg           |
| Content Master Package:                            | 10                |
| Dimensions of Master Package:                      | 1550x390x210 mm   |
| Weight Master Package:                             | 20 kg             |
| Product Line:                                      | Advance Line      |
| Warranty                                           | 5 years           |
| Operating Hours:                                   | 50.000 h L80/B20  |
| Disposal Obligation:                               | ✓                 |
| Customs Tariff Number:                             | 9405119090        |
| Certifications                                     | CE,TÜV,ENEC,LM80  |
| Barcode:                                           | 4250557820194     |
| Power Select: Leistungswahl 55, 60, 65, 70W        |                   |
| Photobiologische Risikogruppe gemäß EN62778: RG1   |                   |
| Einschaltstrom: 43,8A, Dauer: 188µs                |                   |
| Max.Anzahl Leucht./Sich.Automat: B16A: 9, C16A: 12 |                   |

## Information and Downloads:

