

# Xona Maxima Basic Unit 150FF 50-860-8000LM DALI



## Product information "Xona Maxima Basic Unit 150FF 50-860-8000LM DALI"

### LED llinear light system

The Basic Edition is the most cost effective version of the modular Litegear® Maxima LED light line system. With a system efficiency of up to 160 lumens / watt, this system not only convinces with its technical best values but also with a very attractive price. The system consists of a trunking support profile with integrated wiring and connectors for almost tool-free fast mounting and a light module which is locked into the mounting rail. The luminaire modules consist of an electronic ballast, LED boards and optical covers with selectable, different beam angles. The LED modules are available in 4 different light colors: 3000K, 4000K, 5000K and 6000 Kelvin as well as in 3 performance versions: 35W, 50W and 70W. This diversity results in lighting solutions for a wide variety of applications. The support profiles are available up to a length of 3U = 450cm in 3 versions: 5-wire (3 phases), 8-wire (3 phases with Dali / 1-10V and continuous current) and 12-core (3 phases, Dali / 1-10V, emergency lighting). The trunking support profiles can be suspended from the ceiling by means of a steel cable, chain, clip or rod. In addition, special mounting clips for grid ceilings are available. Optionally, the luminaire modules are also available in dimmable version and with battery emergency power supply.

### Application:

- industry and warehouse
- sales areas and exhibition
- office and workshop

### Advantages:

- fast, cost-effective installation
- high power savings through excellent system efficiency > 160lm / W
- long life (70,000h) and very low maintenance costs



### Technical Details:

Luminous Flux	8000 lm
Light Yield:	160 lm/W
Light Temperature:	6000 K
Color Rendering Index (CRI)	≥83 Ra
Color Consistency (SDCM):	4
Power Consumption:	50 W
Power Factor (PF):	0.96
Operating Hours:	>50.000 h L80/B10
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 50°C
Housing Material:	steel
Housing Color	white
Coating:	coated
Dimensions	1498,5x70x39,4 mm
Net Weight:	1680 g
Warranty	5 years

### Information and Downloads:



#### Accessories:

Daylight and motion sensors, corners and branches, dummy modules, end caps, connectors, support modules for escape lights or power outlets