

Modulux Linear LED- Modul 150-35/50-840-8100lm-WH DALI



Technical Details:

| | |
|-----------------------------|-------------------|
| Luminous Flux | 8100 lm |
| Light Yield: | 162 lm/W |
| Light Temperature: | 4000 K |
| Color Rendering Index (CRI) | ≥80 Ra |
| Color Consistency (SDCM): | 4 |
| Power Consumption: | 50 W |
| Power Factor (PF): | 0.95 |
| Operating Hours: | >50.000 h L80/B10 |
| Switching Cycles: | >100.000 |
| Ignition Time: | <0,5 s |
| Ambient Temperature (TA): | -20°C - 45°C |
| Housing Material: | aluminum |
| Housing Color | white |
| Coating: | powder-coated |
| Dimensions | 1490x60x11 mm |
| Net Weight: | 1150 g |
| Warranty | 5 years |

Product information "Modulux Linear LED- Modul 150-35/50-840-8100lm-WH DALI"

Linear LED tracklight for 3-phase trackrails

Elegant, flat LED luminaire with integrated 3-phase track adapter which is completely integrated in the standard track rails. Elegant, ultra flat appearance only 11mm high and 60mm wide. Available with symmetrical 60/90/120° or asymmetrical light dispersion 2 x 45° with multi-lens panel. Ideal for illuminating supermarket shelves, retail areas, exhibition halls, extremely high luminous flux up to 8000 lumens with only 50W consumption corresponding to up to 160 lumens / watt.

- Easy and fast installation using 3-phase trackrail adapters.
- 3 selectable power phases, compatible with all common track systems
- Adjustment output power: Adjustable LED driver 35, 40, 45, 50Watt
- Modular structure of the lens panel
- The individual modules can be seamlessly lined up. It creates the impression of a continuous line of light.
- Good heat dissipation and optimal light distribution
- Also available with dimmable Dali driver on request.
- Available in 2 housing colors: black, white optional also in silver (clarify minimum quantity beforehand)
- Long life LED technology up to 50.000 hours L80/B10

Information and Downloads:



- available in two lengths: 60cm and 150cm