


Order number: LG56216

Fenestra Value Square MKIII 6262 36-840-4350LM IP66 UGR<21, 120lm/W, RAL9003



Technical Details:

Luminous Flux:	4350 lm
LED Output:	35 W
Light Yield:	121 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥82 Ra
Color Consistency (SDCM):	<4
Beam Angle:	110 °
Unified Glare Rating (UGR):	<21
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.96
Input Driver:	terminal
Output of Driver:	DC 30 - 40V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	620x620x12 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	66 (66 room side)
IK Code:	06
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	weather proof
Cover:	opal
Net Weight:	3166 g
Type of Packaging:	box
Dimensions of Packaging:	645x645x45
Weight incl. Packaging:	3.65 kg
Content Master Package:	4
Dimensions of Master Package:	650 x 650 x240 mm
Weight Master Package:	19,4 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80,D
Barcode:	4250557820965
inkl. Klemmdose mit Terminalblock in/out	
Brandschutzklasse UL94-HB	
auch mit dimmbarem Treiber lieferbar	

Information and Downloads:

