
Order number: LG51311

Lifud GDE014YG 200-350mA Triac Dim Driver







Technical Details:

Power Consumption:	14 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h TC<80°C
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	plastic
Housing Color	white
Dimensions	97x46x31 mm
Net Weight:	92 g
Warranty	5 years

Information and Downloads:

Product information "Lifud GDE014YG 200-350mA Triac Dim Driver"

LED Power Supply

GSD040YA series is a 40W DC constant current mode output LED driver featuring the multiple levels selectable by dip switch and the DALI interface with the compliance
to IEC62386-207. GSD040YA operates from 180 to 264VAC and offers different current levels ranging between 350mA and 1050mA. Thanks to the high efficiency up to 87%, with
the fanless design, the entire series is able to operate for -30C° ~+90C° case temperature under free air convection. In addition,GSD040YA is equipped with push dimming, 1-10V / PWM and
synchronization so as to provide the optimal design flexibility for LED lighting system.
LED indoor lighting

Applications:

LED office lighting
LED architectural lighting
LED panel lighting

Product Features:

- Constant Current mode output with multiple levels selectable by dip switch
- Plastic housing with class II design
- Built-in active PFC function
- Standby power consumption < 0.7W
- Functions: DALI interface, push dimming, 1-10V / PWM