


Cetara Office 6060 BAP 36-840-4320LM Dali Push-Dim



Technical Details:

Luminous Flux:	4320 lm
LED Output:	35 W
Light Yield:	120 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 4014
Ignition Time:	<0,5 s
Power Consumption:	36 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 32-42V, 500-1000mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 50°C

Dimensions:	595x595x10 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (44 room side)
IK Code:	02
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	prismatic
Net Weight:	2130 g
Type of Packaging:	box
Dimensions of Packaging:	650x665x35
Weight incl. Packaging:	2.45 kg
Content Master Package:	5
Dimensions of Master Package:	650x200x650 mm
Weight Master Package:	13,3 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557822235
595 x 595mm für Rasterdecken mit 60cm Achsmass	
Europe Design for grid ceiling 60 x 60cm	
inkl. Dali-2 dimmbarer LED-Treiber!	
incl. Dali-2 Dim LED driver!	

