Technical Data Sheet

Order number: LG10075


LITEGEAR
LED Lighting Solutions

Integra SMD MKIII 15-40-830-5100lm max. >125lm/W UGR<19









Technical Details:

Luminous Flux:	5000 lm
LED Output:	39 W
Light Yield:	125 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	83 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Bridgelux
LED-Chip:	SMD 2835
Number of LED:	180
Ignition Time:	<0,5 s
Input Current:	DC 30-42V, 350-1000mA
Power Consumption:	40 W
Output of Driver:	DC 30 - 42V, 350-1000mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-10°C - 40°C

Dimensions:	217x121 mm
Installation Depth:	121 mm
Cut-Out Dimensions:	205 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	44 (65 room side)
IK Code:	08
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	IP65 raumseitig
Cover:	clear
Net Weight:	1070 g
Type of Packaging:	box
Dimensions of Packaging:	240x240x140
Weight incl. Packaging:	1.24 kg
Content Master Package:	10
Dimensions of Master Package:	720x250x500 mm
Weight Master Package:	12,2 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	94051190
Certifications	CE
Barcode:	4250557822747

ohne Vorschaltgerät! bei Zubehör pass. EVG wählen

without power supply! choose one in accessories

IP65 raumseits

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

PMMA Cover/Schutzscheibe