LITEGEAR LED Lighting Solutions

SOLVELA BRICK 6-730-900LM IP65



Product information "SOLVELA BRICK 6-730-900LM IP65"

Solvela Brick SOLAR LED wall light

- Self-sufficient LED wall light with integrated solar panel, asymmetrically radiating LED modules and PIR motion sensor with daylight harvesting
- Ideal for mounting on facades to illuminate walkways or as safety lighting
- BEAM ANGLE. Type. III 140° x 70°
- High light output up to 135 lumen/watt at 6W = 850lm
- Battery: Li-lon
- 2 operating modes:

A: 5% orientation light + 100% light when movement detected @ >30% battery, < 30% battery: off + 100% when movement detected B: max. 5 hours with 50% orientation light and 100% light when motion is detected. When less than 30% battery capacity off + 100% with motion detection

- Maximum battery life: 2-4 nights depending on sunshine, battery status and mode
- Modes and settings changeable.
- Motion sensor with 120° detection range 6m at 2.0-4.0m installation height
- UV-stable, flame-retardant ABS plastic
- maximum mounting height: 4m
- quick, easy installation using screws and dowels (incl.)
- Period of use: approx. 4 years

Applications:

Outside on walls and facades: on outside stairs, garages, sidewalks, as security lighting or for decorative purposes (architectural lighting)







Technical Details:

| Luminous Flux | 900 lm |
|-----------------------------|---------------------------|
| Light Yield: | 150 lm/W |
| Light Temperature: | 3000 K |
| Color Rendering Index (CRI) | ≥80 Ra |
| Color Consistency (SDCM): | 5 |
| Power Consumption: | 6 W |
| Operating Hours: | >15.000 h L80/B20 |
| Switching Cycles: | >15.000 |
| Ignition Time: | <1 s |
| Ambient Temperature (TA): | -10°C - 45°C |
| Housing Material: | ABS+PC, Anti UV,V0 firep. |
| Housing Color | white |
| Dimensions | 230x97x42,7 mm |
| Net Weight: | 0.585 g |
| Warranty | 2 years |

Information and Downloads:

