


JUPITA HighBay 200-830/857-31000LM 1-10V Dim



Technical Details:

Luminous Flux:	31000 lm
Light Yield:	155 lm/W
Light Color:	dualwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	105 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	1-10V,PWM
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 2835
Number of LED:	532
Ignition Time:	<0,5 s
Input Current:	AC 100-277V, 50/60Hz
Power Consumption:	200 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-40°C - 45°C
Storage Temperature:	-40°C - 70°C

Dimensions:	271x215 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	65
IK Code:	08
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Cover:	Lens
Net Weight:	3005 g
Type of Packaging:	box
Dimensions of Packaging:	305x305x205
Weight incl. Packaging:	3.49 kg
Content Master Package:	1
Dimensions of Master Package:	305x305x205 mm
Weight Master Package:	3,5 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557822259
Surge preduct:	L-N: 4KV, L/N-Ground 6KV
beam angle select:	60°, 90°, 105° Zoom
UGR <24, optinal refractor, bracket	
Power select:	100, 150, 200W, 3in1 Dim 1-10V, PWM
CCT select:	3000, 4200, 5700K

Information and Downloads:

