

PARAFLECTA Modul 6-827/850-570LM




Product information "PARAFLECTA Modul 6-827/850-570LM"

Litegear ® universal Retrofit LED-Module suitable for recessed MR16 downlight fittings

One Fit all

perfect replacement for konventional halogen MR16 GU5,3 or GU10 bulbs

- high system efficiency up to 100lm/W (370-570lm)
- selectable output power 4/6W via switch
- CCT selectable 2700, 3000, 4000, 5700 Kelvin via switch
- Triac dimmable with common dimmers
- compact dimensions: 50mm Dimensions: and only 30mm high for recessed ceilings with limited space
- tool free, plugable terminal box for power loop 240V AC, perfect for replacing the driver
- good color rendering index: CRI >80, concentrated light beams: 38°, flicker free light



Technical Details:

Luminous Flux	570 lm
Light Yield:	95 lm/W
Light Temperature:	2700, 3000, 4000, 5700 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	4, 6 W
Operating Hours:	>50.000 h L80/B20
Switching Cycles:	>50.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	Aluminium/plastic
Housing Color	black/white
Coating:	lacquered
Dimensions	50x30 mm
Net Weight:	150 g
Warranty	3 years

Information and Downloads:

