Technical Data Sheet


Order number: LG10400


LITEGEAR®
LED Lighting Solutions

PARAFLECTA Modul 6-827/850-570LM









Technical Details:

Luminous Flux:	570 lm
LED Output:	5.33 W
Light Yield:	95 lm/W
Light Temperature:	2700, 3000, 4000, 5700 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	38 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	"Triac Phasenan-/abschnitt"
LED-Chip:	SMD2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	Power Select (4, 6 W)
Contains Driver:	✓
Driver Manufacturer:	Litegear
Input Driver:	terminal
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	50x30 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	20
IK Code:	10
Housing Color	black/white
Housing Material:	Aluminium/plastic
Coating:	lacquered
Special Feature of Housing:	steckbare Anschlußbox
Cover:	Lens
Net Weight:	150 g
Type of Packaging:	box
Dimensions of Packaging:	100x100x85
Weight incl. Packaging:	0.174 kg
Content Master Package:	32
Dimensions of Master Package:	395x395x290 mm
Weight Master Package:	14,5 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80,ERP
Barcode:	4250557822556
Passend für MR16 Downlightarmaturen	
suitable for MR16 downlight fixtures	
kompatibel mit den meisten Phasenan-/abschnitsdimm	
campatible with most Triac dimmer	
B10: 108x / B16: 170x / C10: 108x / C16: 170x	

Information and Downloads:

