Technical Data Sheet


**Order number: LG14861B**

LITEGEAR
LED Lighting Solutions

# Varia RC Downlight Gehäuse 40W-BK incl. Driver








## Technical Details:

| | |
|---|---|
| **Swappable Reflector:** | ✓ |
| **Input Current:** | AC 200-240V, 50/60Hz |
| **Power Consumption:** | 40 W |
| **Contains Driver:** | ✓ |
| **Driver Manufacturer:** | AGT |
| **Power Factor (PF):** | >0.95 |
| **Input Driver:** | terminal |
| **Output of Driver:** | DC 32-42V, 700-1000mA |
| **CC/CV:** | CC |
| **Output Current Adjustable:** | ✓ |
| **Input Lamp:** | Terminal |
| **Switching Cycles:** | >100.000 |
| **Electrical Protection Class:** | II |
| **Loop-Through Cabling:** | ✓ |
| **Ambient Temperature (TA):** | -10°C - 45°C |
| **Storage Temperature:** | -20°C - 55°C |

| | |
|---|---|
| **Dimensions:** | 189x163 mm |
| **Cut-Out Dimensions:** | 165-185 mm |
| **Mounting:** | Decke |
| **Montageart:** | recessed |
| **Pivot Range pan:** | 355 ° |
| **Pivot Range tilt:** | 30 ° |
| **IP Class:** | 20 |
| **Housing Color** | black |
| **Housing Material:** | aluminum |
| **Coating:** | powder-coated |
| **Special Feature of Housing:** | modular |
| **Net Weight:** | 1580 g |
| **Type of Packaging:** | box |
| **Weight incl. Packaging:** | 1.86 kg |
| **Content Master Package:** | 4 |
| **Dimensions of Master Package:** | 272x550x395 mm |
| **Weight Master Package:** | 7,73 kg |
| **Product Line:** | Premio Line |
| **Warranty** | 5 years |
| **Operating Hours:** | 50.000 h L80/B20 |
| **Disposal Obligation:** | ✓ |
| **Customs Tariff Number:** | 9405119090 |
| **Certifications** | CE,LM80 |
| **Barcode:** | 4250557823263 |

Gehäuse zur Aufnahme von LED-Modul, Linse, Blende

housing to carry LED module, lens and bezel

Power Select: 28, 32, 36, 40 Watt

wechselbarer Frontring

schwenkbar 30°

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de