Technical Data Sheet

Order number: LG59083DA

LITEGEAR
LED Lighting Solutions

RENOVIA 157/36-50-840-6000LM BAP, PMMA, DALI Push Dim







Technical Details:

Luminous Flux:	6000 lm
LED Output:	48 W
Light Yield:	120 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip:	SMD
Number of LED:	96
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	50 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 25-40V, 1250mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1570x360x55 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	40 (53 room side)
IK Code:	03
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	zweiget. Anbaugehäuse
Cover:	Mikroprismatisch PMMA
Net Weight:	5670 g
Type of Packaging:	box
Weight incl. Packaging:	6.61 kg
Content Master Package:	4
Dimensions of Master Package:	1630x372x415 mm
Weight Master Package:	28,65 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	70.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557820781
Dali Push Dim	
PMMA Lightguideplate, anti yellow	
Bildschirmarbeitsplatztauglich DIN EN12464-1	

Information and Downloads:

