


RENOVIA 127/40-840-4800LM BAP, PMMA DALI Push Dim



Technical Details:

Luminous Flux:	4800 lm
LED Output:	39 W
Light Yield:	120 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip:	SMD
Number of LED:	80
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	40 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 32-42V, 1000mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 50°C

Dimensions:	1270x360x45 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	40
IK Code:	04
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	zweigert. Anbaugehäuse
Cover:	Mikroprismatisch PMMA
Net Weight:	5500 g
Type of Packaging:	box
Weight incl. Packaging:	6.5 kg
Content Master Package:	4
Dimensions of Master Package:	1330x375x420 mm
Weight Master Package:	23,78 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,D
Barcode:	4250557820798
inkl. 5-pol. Terminal Klemmblock	
inkl. 5-pole terminal block	
PMMA Lightguideplate, anti yellow	
blendfrei: Bildschirmarbeitsplatztauglich	
Flickerfree, Dali Push Dim	

Information and Downloads:

