

ENCORA-LINE 1500-55-CCT-6600LM BEG 120lm/W



Technical Details:

Luminous Flux:	6600 lm
LED Output:	50 W
Light Yield:	120 lm/W
Light Temperature:	4000,5000,6500 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	Power Select (27/55 W)
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 60°C

Dimensions:	1500x61x73,5 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	08
Housing Color	white
Housing Material:	Polycarbonat
Coating:	UV geschützt
Special Feature of Housing:	Through-wiring
Cover:	frosted
Net Weight:	1200 g
Type of Packaging:	box
Dimensions of Packaging:	1505x161x202
Weight incl. Packaging:	1.48 kg
Content Master Package:	6
Dimensions of Master Package:	1517x173x226 mm
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405423100
Certifications	CE,LM80,ERP
Barcode:	4250557823492
Schnellverschlüsse	
connectable to build a light line	
Durchgangsverdrahtung/wire trough 3 x 1,5mm ²	
CCT Select: 4000, 5000, 6500 kelvin	
Power Select: Ausgangsleistung umschaltbar 50/100%	

Information and Downloads:

