

SOLVELA SWING 15-CCT730/740-2000LM IP65



Technical Details:

Luminous Flux:	2000 lm
LED Output:	15 W
Light Yield:	133 lm/W
Light Temperature:	3000, 4000 K
Light Color:	CCT Select
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<5
Beam Angle:	95x85 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	112
Ignition Time:	<1 s
Input Current:	DC 3,2V, 6000mAhmA
Power Consumption:	15 W
CC/CV:	CV
Switching Cycles:	>20.000
Ambient Temperature (TA):	-10°C - 45°C
Storage Temperature:	0°C - 50°C

Dimensions:	228x95x43 mm
Mounting:	Wand
Montageart:	surface mounted
IP Class:	65
Housing Color	black
Housing Material:	ABS+PC, Alu Anti UV
Special Feature of Housing:	Sensor 8m /Solarpanel
Cover:	Reflector
Net Weight:	1190 g
Type of Packaging:	box
Weight incl. Packaging:	1.38 kg
Content Master Package:	24
Dimensions of Master Package:	490x320x223 mm
Weight Master Package:	15,18 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405413100
Certifications	CE
Barcode:	4250557824321
Solarleuchte für Wandmontage, modernes Design	
solar wall pack light stylish design, 2 work modes	
integrierter Bewegungssensor mit Dimmung/Standby	
integrated motion sensor 120° <6m	
replaceable battery pack, max. instal. height: 4m	

Information and Downloads:

