Technical Data Sheet

Order number: LG11995

SOLVELA FLOOD 20-740-3400LM IP65 IR remote







Technical Details:

Luminous Flux:	3400 lm
Light Yield:	170 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<6
Beam Angle:	140x68 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	DC 10V, 12AHmA
Power Consumption:	20 W
CC/CV:	CV
Input Lamp:	plug connector
Switching Cycles:	>25.000
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-10°C - 50°C

Dimensions:	621,6x289,7x73,6 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
Housing Color	grey
Housing Material:	aluminum
Special Feature of Housing:	Sensor sep. Solarpanel
Cover:	Lens
Net Weight:	4980 g
Type of Packaging:	box
Dimensions of Packaging:	730x330x100
Weight incl. Packaging:	5.81 kg
Content Master Package:	4
Dimensions of Master Package:	760x395x360 mm
Weight Master Package:	25,28 kg
Product Line:	Advance Line
Warranty	2 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405413990
Certifications	CE
Barcode:	4250557823126
Bügel für Wand-/Deckenmontage	
separates Solarpanel, Sensor mit Fernbedienung	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de