Technical Data Sheet

Order number: LG51251

Lifud LF-GMR075YV024A CV Power supply Flicker free



Technical Details:

Ignition Time:	<0,5 s
Power Consumption:	75 W
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 24V, 3125mA
CC/CV:	CV
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-30°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	285x30x21 mm
Montageart:	surface mounted
IP Class:	20
Housing Color	Alu/blue
Housing Material:	steel
Coating:	verzinkt
Special Feature of Housing:	plasticabdeckungen
Net Weight:	265 g

Product Line:	Advance Line
Warranty	5 years
Disposal Obligation:	✓
Customs Tariff Number:	8504408390
Certifications	CE
Netzteil für LED-Strips oder andere Leuchtmedium	
power supply for LED strips and bulbs	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de