

Lifud LF-GMR045YV024A CV Driver Flicker free



Lifud
LED Driver



Product information "Lifud LF-GMR045YV024A CV Driver Flicker free"

LED Power Supply

The Lifud LF-GMR045YV024A is an extremely versatile power supply for all kinds of passive LED projectors and strips. You can use it indoor installations such as cove lighting or inside linear luminaires.

Product Features:

- usable for all DC 24V single-colour LED strips and LED bulbs

Technical Details:

- Mains input: AC 220 - 240V, 47 - 63Hz (max. 200 - 264V AC)
- Housing: steel with plastic covers
- Output voltage: DC 24V +/-0,5V, constant voltage
- Rated power: 1,88A
- Output power: 45W
- Dimmable: no
- Protection: short circuit, over load, over voltage
- Scope: LED strips and Illumination
- Safety standars: SELV, TÜV, CE, CB
- Power Faktor: >0,95
- Efficiency: 88%

Technical Details:

Power Consumption:	45 W
Power Factor (PF):	0.95
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-30°C - 50°C
Housing Material:	steel
Housing Color	Alu/blue
Coating:	verzinkt
Dimensions	245x30x21 mm
Net Weight:	205 g
Warranty	5 years

Information and Downloads:

