Technical Data Sheet

Order number: LG50364

Kompakter Driver für Panel und Downlights

Technical Details:

Input Current:	AC 220-240V, 50/60Hz, DC 170-276V
Power Consumption:	44 W
Driver Manufacturer:	KGP
Power Factor (PF):	>0.92
Input Driver:	terminal
Output of Driver:	DC 27-45V, 700-1050mA
CC/CV:	CC
Output Current Adjustable:	✓
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 50°C

Dimensions:	137,5x44x23 mm
Montageart:	recessed
IP Class:	20
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	ohne Zuentlastung
Net Weight:	83 g
Weight incl. Packaging:	0.083 kg
Content Master Package:	100
Dimensions of Master Package:	400x235x150 mm
Weight Master Package:	8,59 kg
Product Line:	Advance Line
Warranty	5 years
Customs Tariff Number:	8504408390
Certifications	CE,ENEC,SELV
Barcode:	4250557823676
Power Select: 350-700mA in 50mA Schritte	
perfect for LED panels and downlights	
max. driver on 16A breaker: B Type: 23,C Type: 37	

Information and Downloads: