

Xona Area 1500-50-840-6800LM



Technical Details:

Luminous Flux:	6800 lm
LED Output:	49 W
Light Yield:	128 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	130 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz, DC 180-240V
Power Consumption:	53 W
Contains Driver:	✓
Power Factor (PF):	>0.97
Input Driver:	terminal
Output of Driver:	DC 113-126V, 420mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	1500x141x60 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	44
IK Code:	08
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	prismatischen Abdeckung
Cover:	opal
Net Weight:	750 g
Type of Packaging:	box
Dimensions of Packaging:	1530x155x80
Weight incl. Packaging:	0.9 kg
Content Master Package:	4
Dimensions of Master Package:	1570x405x195 mm
Weight Master Package:	3,6 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	94051990
Certifications	CE
Barcode:	4250557822679
optional Bewegungssensor und Batterienotstrommodul	
motion sensor and emergency battery power optional	
THD: 5%	
DC Notstromfähig, Master-Slave Funktion optional	
Ersatztreiber: SBL-D60	

Information and Downloads:



