
Technical Data Sheet

Order number: LG5502

Element DALI DT8 Dimmer RGB + DUAL-White







Technical Details:

Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
Input Current:	DC 12-36V
Power Consumption:	900 W
Driver Manufacturer:	Litegear
Input Driver:	terminal
Output of Driver:	DC 12-36V, 5000mA
CC/CV:	CV
Switching Cycles:	>50.000
Electrical Protection Class:	III
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-20°C - 60°C

Dimensions:	170x59x29 mm
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	plastic
Net Weight:	200 g
Zones:	1
Channels:	5
Dimming:	0,1-100%
Product Line:	Advance Line
Warranty	2 years
Disposal Obligation:	✓
Customs Tariff Number:	8537109199
Certifications	CE,TÜV
Barcode:	4250557825281
Dali DT8 RGB/WW+CW (RGB + Dualwhite)	
max. 5 x 5A= 4 x 60-180W/Ch. (12-36V)	
2mA Dali consumption/Verbrauchslast	
Set up Menü/menu	
Dimming range: 0,1-100%	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de