


CIELLA MEDI LED-Unit 14-827/840-WH 1570lm IP44



Technical Details:

Luminous Flux:	1570 lm
LED Output:	13 W
Light Yield:	120 lm/W
Light Temperature:	2700, 3000, 4000 K
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	120 °
Light Emission:	downward
LED-Chip Manufacturer:	MTC
LED-Chip:	Epistar
Number of LED:	40
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	Power Select (8, 10, 12, 14 W)
Contains Driver:	✓
Driver Manufacturer:	AGT
Power Factor (PF):	>0.9
Input Driver:	Kabel mit Terminal
Output of Driver:	DC 20-40V, 200-350mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	cable with plug
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 60°C

Dimensions:	75x41 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (44 room side)
IK Code:	08
Housing Color	white
Housing Material:	Aluminium+PC
Coating:	lacquered
Special Feature of Housing:	schraubbares Modul
Cover:	opal
Net Weight:	271 g
Type of Packaging:	box
Dimensions of Packaging:	130x105x55
Weight incl. Packaging:	0.307 kg
Content Master Package:	36
Dimensions of Master Package:	410x403x190 mm
Weight Master Package:	11,36 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	54.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557827438
CCT Select:	2700, 3000, 4000K
Power Select:	8, 10, 12, 14W
elektr. Anschlußdose für Durchgangsverdrahtung	
modulare Aufbau, kombinierbar mit kon.Deckenringen	
1570lm@3000k and 13W	

Information and Downloads:

