

Order number: LG10469

Axea XL 40-930-3640-5080LM max. incl.Treiber 700-1050ma 132lm/m/W GEG



Product information "Axea XL 40-930-3640-5080LM max. incl.Treiber 700-1050ma 132lm/m/W GEG"

LED Downlight

Axea Eco

Normally you find many downlights equipped with 70W HQI discharge lamps in shops. Now you can replace those ones with the Litegear® Axea Eco LED downlight and save over 60% costs for electricity. The beamangle is 36°, ideally for lighting up big areas from short distance. The long lifespan will save a lot of follow up cost for light bulbs as you have them with traditional lights. Axea Eco is available in different light colours. We offer separate optics in 12° and 24° for this series often used in museums or for a dynamic product presentation.

The stylish, timeless housing is generally painted in white but can be made in silver or black color on demand. LED luminaires from Litegear make your cost calculate able and produce less CO² for a greener environment. LED light produces much less heat, good to reduce costs for air condition to cool your surrounding. The heat of the chips can dissipate through big aluminum heat sinks with out any fan to avoid dust coming into the luminaire.

Applications:

- Shop
- Gas station shop
- Museum
- Supermarket
- Car showroom

Technical Details:

| | |
|-----------------------------|-------------------|
| Luminous Flux | 5080 lm |
| Light Yield: | 127 lm/W |
| Light Temperature: | 3000 K |
| Color Rendering Index (CRI) | ≥90 Ra |
| Color Consistency (SDCM): | 3 |
| Power Consumption: | 30-40 W |
| Power Factor (PF): | 0.95 |
| Operating Hours: | >50.000 h L80/B20 |
| Switching Cycles: | >100.000 |
| Ignition Time: | <0,5 s |
| Ambient Temperature (TA): | -20°C - 45°C |
| Housing Material: | aluminum |
| Housing Color | white |
| Coating: | lacquered |
| Pivot Range pan: | 350 ° |
| Pivot Range tilt: | 80 ° |
| Dimensions | 190x155 mm |
| Cut-Out Dimensions | 175 mm |
| Net Weight: | 1453 g |
| Warranty | 5 years |

Information and Downloads:

