


Order number: LG10469

# Axea XL 40-930-3640-5080LM max. incl. Treiber 700-1050ma 132lm/m/W GEG



## Technical Details:

Luminous Flux:	5080 lm
Light Yield:	127 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	38 °
Light Emission:	downward
LED-Chip Manufacturer:	JUN CAN
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	Power Select (30-40 W)
Contains Driver:	✓
Driver Manufacturer:	KGP
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 25-40V, 700-1050mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 45°C

Dimensions:	190x155 mm
Installation Depth:	175 mm
Cut-Out Dimensions:	175 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range pan:	350 °
Pivot Range tilt:	80 °
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	clear
Net Weight:	1453 g
Type of Packaging:	box
Weight incl. Packaging:	1.547 kg
Content Master Package:	12
Dimensions of Master Package:	590x395x365 mm
Weight Master Package:	19,60 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557825458
Power Select:	28-40W
Sehr gute Farbwiedergabe CRI>90Ra	

