

Retrova 1550 54-840-7020LM



Technical Details:

Luminous Flux:	7020 lm
LED Output:	49 W
Light Yield:	130 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥82 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Unified Glare Rating (UGR):	<28
Light Emission:	downward
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 2835
Number of LED:	272
Ignition Time:	<0,5 s
Input Current:	AC 198 - 264V, 370mA, 50/60Hz
Power Consumption:	Power Select (45, 52, 55W W)
Contains Driver:	✓
Driver Manufacturer:	KGP
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 20-50V, 900-1800mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 60°C

Dimensions:	1568x100x82 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	grey
Housing Material:	Polycarbonat
Special Feature of Housing:	304 Edelstahl Clips
Cover:	prismatic
Net Weight:	1950 g
Type of Packaging:	box
Dimensions of Packaging:	1580x110x85
Weight incl. Packaging:	2.3 kg
Content Master Package:	6
Dimensions of Master Package:	1595x280x225 mm
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,SELV
Barcode:	4250557810447
KGP Treiber	
Anzahl Leuchten:	10B: 13,16B: 20, 10C: 19, 16C: 30

