
Technical Data Sheet


Order number: LG14390RGBWS

LITEGEAR
LED Lighting Solutions

DURATA LINE 80-RGBW-WFL DMX512 Control 8000lm









Technical Details:

Luminous Flux:	8000 lm
LED Output:	80 W
Light Yield:	120 lm/W
Light Temperature:	3000 K
Light Color:	RGBWW
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	101 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DMX
LED-Chip Manufacturer:	Sanan
LED-Chip:	SMD 5050
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 0,4mA, 50/60Hz
Power Consumption:	80 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	lighting track
Output of Driver:	DC 24V, 1500mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-25°C - 35°C

Dimensions:	2800x50x60 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20 (20 room side)
IK Code:	05
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular
Cover:	opal
Net Weight:	4000 g
Type of Packaging:	box
Dimensions of Packaging:	2820x60x140
Weight incl. Packaging:	5 kg
Content Master Package:	4
Dimensions of Master Package:	2820x60x140 mm
Weight Master Package:	20 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405219090
Certifications	CE
Barcode:	4250557826967

Elegante Lichtlinienleuchtez.B. für Aerobicräume

Mio. von Farben generierbar über RGBWW

Farbmischung und Dimmung über DMX512 4Ch.

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Information and Downloads: