


Wega Circle 600-60-830-5800LM DALI DIM



Technical Details:

| | |
|------------------------------|------------------------|
| Luminous Flux: | 5800 lm |
| Light Yield: | 97 lm/W |
| Light Temperature: | 3000 K |
| Light Color: | warmwhite |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <4 |
| Beam Angle: | 110 ° |
| Unified Glare Rating (UGR): | <22 |
| Light Emission: | downward |
| Dimmable: | ✓ |
| Method of Dimming: | DALI |
| LED-Chip: | SMD 2835 |
| Ignition Time: | <0,5 s |
| Input Current: | AC 220 - 240V, 50/60Hz |
| Power Consumption: | 60 W |
| Contains Driver: | ✓ |
| Driver Manufacturer: | AAA |
| Power Factor (PF): | >0.9 |
| Input Driver: | terminal |
| CC/CV: | CC |
| Input Lamp: | Terminal |
| Switching Cycles: | >100.000 |
| Electrical Protection Class: | II |
| Ambient Temperature (TA): | -20°C - 45°C |
| Storage Temperature: | -20°C - 55°C |

| | |
|--|------------------|
| Dimensions: | 600x65 mm |
| Mounting: | ceiling,wall |
| Montageart: | surface mounted |
| IP Class: | 20 |
| IK Code: | 03 |
| Housing Color | black |
| Housing Material: | aluminum |
| Coating: | powder-coated |
| Cover: | prismatic |
| Net Weight: | 5200 g |
| Type of Packaging: | box |
| Dimensions of Packaging: | 645x80x630 |
| Weight incl. Packaging: | 6.1 kg |
| Content Master Package: | 2 |
| Dimensions of Master Package: | 650x185x655 mm |
| Weight Master Package: | 13,3 kg |
| Product Line: | Advance Line |
| Warranty | 5 years |
| Operating Hours: | 50.000 h L80/B20 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405423990 |
| Certifications | CE,SELV |
| Barcode: | 4250557823218 |
| mit opt. Zubehör als Pendelleuchte zu verwenden | |
| Can be used with opt. accessories as pendant light | |
| Fangseil und Drehhalterung | |
| dimmbarer 0-10V Treiber | |

Information and Downloads:



