


Lucello Multi-CCT BL-Panel 6262-40-830/840-5000LM BAP UGR<19



Product information "Lucello Multi-CCT BL-Panel 6262-40-830/840-5000LM BAP UGR<19"

LED Backlight Panel

Litegear® Lucello LED-Panel for German grid ceilings 62,5 x 62,5cm
 For computer workstations - suitable according to EN 12464-1 for screens with high luminance!

- Very low power consumption and high system efficiency: 125lm/W
- Power Select: electronic driver with select able output power: 28, 32, 36, 40W
- CCT Select: select able light colour by switch on the panel backside: 3000, 3500, 4000 Kelvin
- Replacement for traditional troffer lights: 4 x 18W T8 fluorescent tubes
- excellent price/performance ratio, fast ROI
- Diffusor made from UV stabilized PS
- wide beam angle and very uniform light distribution

Applications:

Shops, corridors, production areas, storage rooms, warehouse, dressing rooms, health club, Fitness, meeting rooms, school

Technical Details:

Luminous Flux	5000 lm
Light Yield:	125 lm/W
Light Temperature:	3000,3500,4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	28,32,36,40 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h L80/B20
Switching Cycles:	>50.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-10°C - 40°C
Housing Material:	steel
Housing Color	white
Coating:	powder-coated
Dimensions	620x620x35 mm
Net Weight:	1960 g
Warranty	5 years

Information and Downloads:

