Technical Data Sheet

Order number: LG65045

Lucello Multi-CCT BL-Panel 6262-40-830/840-5000LM BAP UGR<19





Technical Details:

Luminous Flux:	5000 lm
Light Yield:	125 lm/W
Light Temperature:	3000,3500,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip:	SMD
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	Power Select (28,32,36,40 W)
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 32-42V, 700-1000mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 60°C

Dimensions:	620x620x35 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	30 (44 room side)
IK Code:	02
Housing Color	white
Housing Material:	steel
Coating:	powder-coated
Cover:	prismatic
Net Weight:	1960 g
Type of Packaging:	box
Dimensions of Packaging:	643x665x45
Weight incl. Packaging:	2.6 kg
Content Master Package:	5
Dimensions of Master Package:	650x686x255 mm
Weight Master Package:	12,85 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,D
Barcode:	4250557823522
Bildschirmarbeitsplatz tauglich nach EN 12464-1	
CCT-Select: schaltbare Lichtfarbe 3000,3500,4000K	
Power Select: 28, 32, 36, 40W Treiber einstellbar	
Backlite Technology	
OneFitAll	

Information and Downloads:

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de