

# TARONA 120-36-CCT-Select 4340lm 120lm/W BEG



## Product information "TARONA 120-36-CCT-Select 4340lm 120lm/W BEG"

elegant, halfround LED battenlight

- stylish and easy installing LED battenlight with invisible mounting clips
- sliding mounting clips for screw installation
- power feed in and through from middle and sides with flexible cable and terminal block for through wiring
- Wide homogenous light distribution 120° and good system efficiency of >120lm/W
- integrated LED driver and CCT select switch: 3000K, 4000K, 5000K
- integrated driver with power select 18, 28, 36W
- Easy installation with screws on concrete, wood or plasterboard ceilings

### Applications:

office, school, health care, Fitness, nursing homes, hospital, university, storage rooms

## Technical Details:

Luminous Flux	4340 lm
Light Yield:	121 lm/W
Light Temperature:	3000,4000, 4500, 5000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	18, 28, 36 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h L80/B20
Switching Cycles:	>50.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	Aluminium + PC
Housing Color	white
Coating:	powder-coated
Dimensions	1200x79x44 mm
Net Weight:	650 g
Warranty	3 years

Information and Downloads:

