

# TARONA 120-36-CCT-Select 4340lm 120lm/W BEG



## Technical Details:

Luminous Flux:	4340 lm
Light Yield:	121 lm/W
Light Temperature:	3000,4000, 4500, 5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 150mA, 50/60Hz
Power Consumption:	Power Select (18, 28, 36 W)
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1200x79x44 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
IK Code:	08
Housing Color	white
Housing Material:	Aluminium + PC
Coating:	powder-coated
Special Feature of Housing:	halbrund, rückseit.offen
Cover:	opal
Net Weight:	650 g
Dimensions of Packaging:	1240x470x850
Weight incl. Packaging:	0.81 kg
Content Master Package:	9
Dimensions of Master Package:	1240x280x170 mm
Weight Master Package:	7,91 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,SELV
Barcode:	4250557824550
CCT Select: 3000, 4000, 4500, 5000 Klevin	
Leistungswahlschalter 18, 28, 36W	
>120lm/W Systemleistung	
leichte Montage, universell einsetzbar	

Information and Downloads:

