Product Information

**Order number: LG14910**

# TRABES 120-34-CCT-4080lm 120lm/W BEG









## Product information "TRABES 120-34-CCT-4080lm 120lm/W BEG"

elegant LED batten light

- Stylish and easy surface mounting LED batten light
- Consisting of 2 housing parts: trunk installation housing and optical part. Both will be joined together by internal mechanical spring clips
- Power feed in and through from middle and sides
- Low glare rating, optical prismatic diffusor design for computer work places, UGR< 19 with homogenous light distribution
- Integrated LED driver and CCT select switch: 3000K, 3500K, 4000K
- Easy installation with screws on concrete, wood or plasterboard ceilings

Applications:
office, school, health care, fitness, nursing homes, hospital, university, storage rooms

## Technical Details:

| | |
|---|---|
| **Luminous Flux** | 4080 lm |
| **Light Yield:** | 120 lm/W |
| **Light Temperature:** | 3000,3500,4000 K |
| **Color Rendering Index (CRI)** | ≥80 Ra |
| **Color Consistency (SDCM):** | 4 |
| **Power Consumption:** | 34 W |
| **Power Factor (PF):** | 0.95 |
| **Operating Hours:** | >50.000 h L80/B10 |
| **Switching Cycles:** | >100.000 |
| **Ignition Time:** | <0,5 s |
| **Ambient Temperature (TA):** | -15°C - 50°C |
| **Housing Material:** | Aluminium + PC |
| **Housing Color** | white |
| **Coating:** | powder-coated |
| **Dimensions** | 1200x80x63,5 mm |
| **Net Weight:** | 1670 g |
| **Warranty** | 5 years |

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de