



TRABES 120-34-CCT-4080lm 120lm/W BEG



• Dimension



• Photometry Curve



Technical Details:

Luminous Flux:	4080 lm
Light Yield:	120 lm/W
Light Temperature:	3000,3500,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	520
Ignition Time:	<0,5 s
Power Consumption:	34 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 28-42V, 750mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-15°C - 50°C
Storage Temperature:	-25°C - 55°C

Dimensions:	1200x80x63,5 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
IK Code:	03
Housing Color	white
Housing Material:	Aluminium + PC
Coating:	powder-coated
Special Feature of Housing:	2-teilig
Cover:	clear prismatic
Net Weight:	1670 g
Dimensions of Packaging:	1215x9x75
Weight incl. Packaging:	1.87 kg
Content Master Package:	6
Dimensions of Master Package:	1230x240x205 mm
Weight Master Package:	12,47 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405 11 90 90
Certifications	CE,SELV
Barcode:	4250557824512
CCT Select:	3000, 3500, 4000 K
geeignet für Bildschirmarbeitsplätze	
120lm/W Systemleistung	

Information and Downloads:

