Technical Data Sheet

Order number: LG14912


LITEGEAR
LED Lighting Solutions

TRABES 150-40-CCT-4800lm 120lm/W BEG






• Dimension



Product Name	A	B	C
120cm/4ft	1200	80	63.5
150cm/5ft	1500	80	63.5
180cm/6ft	1800	80	63.5

Unit:mm

• Photometry Curve



Technical Details:

Luminous Flux:	4800 lm
Light Yield:	120 lm/W
Light Temperature:	3000,3500,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	624
Ignition Time:	<0,5 s
Power Consumption:	40 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 28-42V, 1000mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-15°C - 50°C
Storage Temperature:	-25°C - 55°C

Dimensions:	1500x80x63,5 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
IK Code:	03
Housing Color	white
Housing Material:	Aluminium + PC
Coating:	powder-coated
Special Feature of Housing:	2-teilig
Cover:	clear prismatic
Net Weight:	2000 g
Dimensions of Packaging:	1511x90x75
Weight incl. Packaging:	2.26 kg
Content Master Package:	6
Dimensions of Master Package:	1530x240x205 mm
Weight Master Package:	14,47 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405 11 90 90
Certifications	CE,SELV
Barcode:	4250557824529
CCT Select: 3000, 3500, 4000 Klevin	
geeignet für Bildschirmarbeitsplätze	
120lm/W Systemleistung	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

