Technical Data Sheet

Order number: LG60061


LITEGEAR
LED Lighting Solutions

Velocity Blade 24 1,5-857-150lm AST WH









Technical Details:

LED Output:	1.4 W
Light Temperature:	5700 K
Color Consistency (SDCM):	<6
Light Emission:	
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220-240VV, 70mA, 50/60Hz
Power Consumption:	2 W
Contains Driver:	✓
Power Factor (PF):	>0.5
Input Driver:	terminal
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	0°C - 40°C
Storage Temperature:	-10°C - 50°C

Dimensions:	282x352x247 mm
Mounting:	Decke
Pivot Range tilt:	90 °
IP Class:	20
IK Code:	07
Housing Color	white
Housing Material:	Polycarbonat/PMMA
Special Feature of Housing:	Built-in/built-on housing
Cover:	clear
Net Weight:	520 g
Luminaire Type:	Rettungszeichenleuchte
Viewing Distance EN1838:	≥24 m
Sign Visible from Both Sides:	
Included Signs:	Pfeil oben
Testing Facility:	automatischer Selbsttest
Battery Warranty:	3
Discharge Duration:	≥3 h
Battery Type:	Li-Ion
Battery Current:	2500 mA
Battery Charge Duration:	8 h
Initial Charge Duration:	16 h
Charging Power Consumption:	5 W
Battery Cell Quantity	1
Standards for emergency luminaires:	DIN EN 60598-2-22, DIN EN 62034: 2012, Zeichen nach ISO 7010, Anforderung nach DIN EN 50172
Certified By:	LIA
Type of Packaging:	box

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Content Master Package:	10
Dimensions of Master Package:	420x304x247 mm
Weight Master Package:	8,2 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4260733770434
Einschaltstrom Inrush current: 9A/280us @230vac	
autom. Selbsttest: 30s /Woche, Langzeit: 1 x year	
auto selftest: weekly 30s, long duration: 1 x year	
Über- und Entladeschutz, greene Status LED, Taster	