

Vienna Square Wall Light UP/Down 2 x GU10 IP65



Technical Details:

| | |
|---------------------------|------------------------------|
| Light Emission: | |
| Dimmable: | ✓ |
| Method of Dimming: | "Triac Phasen-an-/abschnitt" |
| Input Driver: | terminal |
| Input Lamp: | Terminal |
| Ambient Temperature (TA): | -20°C - 45°C |
| Storage Temperature: | -40°C - 60°C |

Information and Downloads:



| | |
|--|--------------------------|
| Dimensions: | 91x67x165 mm |
| Mounting: | Wand |
| Montageart: | surface mounted |
| IP Class: | 65 |
| IK Code: | 06 |
| Housing Color | black |
| Housing Color (RAL Code): | similar 9005 |
| Housing Material: | aluminum |
| Coating: | powder-coated |
| Special Feature of Housing: | Glasabdeckung oben unten |
| Net Weight: | 682 g |
| Type of Packaging: | box |
| Weight incl. Packaging: | 0.757 kg |
| Content Master Package: | 12 |
| Dimensions of Master Package: | 400x315x215 mm |
| Weight Master Package: | 9,17 kg |
| Product Line: | Advance Line |
| Warranty | 5 years |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405499090 |
| Certifications | CE |
| Barcode: | 4250557824178 |
| Direkte und indirekte Ausleuchtung | |
| für 2 x GU10 LED-Leuchtmittel 50*60mm | |
| Anschlußklemme und Kabeleinführung für 230V in/out | |
| wetterfestes, hochwertiges Alugehäuse pulverbesch. | |