

KUBIX 10-930-32-750LM DIM



Technical Details:

Luminous Flux:	750 lm
LED Output:	9 W
Light Yield:	73 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥95 Ra
Color Consistency (SDCM):	<3
Beam Angle:	32 °
Unified Glare Rating (UGR):	<16
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	"Triac Phasen-an-/abschnitt"
LED-Chip Manufacturer:	Bridgelux 3535
LED-Chip:	High-Power
Number of LED:	4
Ignition Time:	<0,5 s
Power Consumption:	10 W
Contains Driver:	✓
Driver Manufacturer:	Kegu
Power Factor (PF):	>0.93
Input Driver:	terminal
Output of Driver:	DC 12V, 700mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II

Dimensions:	67x67x85 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
Housing Color	white/black
Housing Material:	aluminum
Special Feature of Housing:	kein.sichtbaren Schrauben
Cover:	Lens
Net Weight:	330 g
Type of Packaging:	box
Weight incl. Packaging:	0.364 kg
Content Master Package:	40
Dimensions of Master Package:	420x335x210 mm
Weight Master Package:	14,88 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557823003
Ideal für Wohnräume und Büro	
Perfect for residential applications and office	
Geringe Blendung und gerichtetes Licht	
Low glare rate and concentrated light beams	

Storage Temperature:	-20°C - 50°C
----------------------	--------------

Information and Downloads:

